

"eSigno" access control systems

Door units

ZÁKLADNÍ KONFIGURACE SE ZÁMKEM ANTIPANIC 5A300.60 S FUNKCÍ „NERUŠIT“ MANUÁLNÍM ZAMYKÁNÍM ZE VNITŘ OTOČENÍM SEGMENTU CYLINDRICKÉ VLOŽKY

CONFIGURATION WITH MANUAL DEADBOLT (5A300/5A400 series) WITH PRIVACY FUNCTION

Configuration with CISA 5A300/5A400 mechanical lock (APH 3 locks with split spindle and anti-picking system).

ELECTRONIC PRIVACY FUNCTION activated and **DEADBOLT THROWN** from the inside thumb turn.



A version with white plastic covers is available as standard only if explicitly stated as such. Otherwise, white plastic covers are available as optional accessory

Door thickness: 35mm --> 60mm

centre distance: 70, 72, 85mm



Backset** 40mm --> 90mm (** with backset 40, 45, 50 mm, an APH1 52830 mechanical lock is required for the configuration at an extra charge of 15€)

Emergency opening cylinder: 10G308 cylinder

Square spindle: 8mm

Door unit with CISA 5A300/400 mechanical lock, EU profile cylinder, manual deadbolt, 85mm centre distance

Complete door unit with basic configuration (Classic handle)

Description	Item
  <p>Satin Silver eSigno, Classic handle*</p> <p>5A755XX series lock</p> <p>Keyed alike cylinder</p> <p>Thumb turn</p> <p>Square spindle set</p> <p>Strike plate</p>	<p>1A0M07000M1</p> <p>1 5A30x XX X</p> <p>10G308HX000TPKA</p> <p>106353020XX</p> <p>107457010 / 20 / 30</p> <p>1 06106XX 0 20 /</p> <p>1 0624300 0 12</p>

Panic function locks with APH3 manual deadbolt



Technical features

- Detachable faceplate and painted satin brass strike plate
- Zinc-plated steel case
- Nickel-plated, non-handed latch
- Nickel-plated anti-picking device (if any)
- Nickel-plated 16 mm deadbolt.
- Galvanized steel internal component

Supplied as standard:

Fixing screws
Instruction sheet

On request:

- Faceplate and satin stainless steel strike plate (fin. • Bronze-plated steel (fin. 20)

Standards

- UL R 14945(N) fire resistance, only for satin stainless steel finishes (fin. 20)


Hand:

0 = non-handed

1 = right hand inwards

2 = left hand inwards



Description	Item
FOR ENTRANCE DOORS	
Rounded faceplate	
 <ul style="list-style-type: none"> • With deadbolt and deadlocking latch • Strike plate to be ordered separately • Throws: 1) • Centre distance: 85 mm • Faceplate: 22 mm 	<p>backset 60</p> <p>backset 70</p> <p>backset 80</p>
	<p>1 5A300 60 0</p> <p>1 5A300 70 0</p> <p>1 5A300 80 0</p>

VOLITELNÁ KONFIGURACE SE SAMOZAMYKACÍM ZÁMKEM 5A504.60 S FUNKCÍ „NERUŠIT“ POMOCÍ TLAČÍTKA NA VITŘNÍM KOVÁNÍ

CONFIGURATION WITH AUTOMATIC DEADBOLT and DPR (5A504/5 series) WITH PRIVACY FUNCTION

Configuration with CISA 5A504/5 mechanical lock (with DPR function).

Audit trail of door events including mechanical key override. **ELECTRONIC PRIVACY FUNCTION INCLUDED, ACTIVATED BY A BUTTON.**

The audit trail also records any time during which the deadbolt is NOT operated.

A version with white plastic covers is available as standard only if explicitly stated as such. Otherwise, white plastic covers are available as optional accessory

Door thickness: 35mm --> 79mm

centre distance: 85mm

Backset: 60mm --> 90mm

10G304 emergency opening single cylinder

Square spindle: 8mm

Description	Item
Complete door unit, basic configuration (Classic handle, ISO B)	
 	Satin Silver eSigno, Classic handle* 1A0M01000M1 1 5A504 XX X 1 0G304 XX 0 66 00 KB 107457010 /20 /30 1 06106XX 0 20 / 1 0624300 0 12
5A504XX series lock	
Keyed alike single cylinder	
Square spindle set	
Strike plate	



Mechanical locks (automatic deadbolt, DPR)



Technical features

- Nickel-plated brass, non-handed, antifriction, 17 mm latch.
- Square spindle: 8mm
- Automatic 16 mm deadbolt (5A504/5 series) with door closure detection device (patent EP 1 030 955). 25 mm deadbolt available on request (5A502/5 series).
- Pre-set for mechanical override cylinder.
- Emergency mechanical override detector (events recorded in the Wave Mode and eSigno audit trail)
- Deadbolt status detector (withdrawn or thrown) for lock status recognition and event recording in the Wave Mode and eSigno audit trail

- Faceplate in protected satin brass (fin. 00) or satin nickel-plated brass (fin. 12).
- Strike plate available on request.
- Stainless steel finish (fin. 20) 3-hour fire resistance rating available on request Fixing screws

Description	Item
 <ul style="list-style-type: none"> • Rounded faceplate in protected satin brass • 16mm deadbolt • Faceplate: 22 mm • Throws: 1) • Centre distance: 85 mm 	backset 60 backset 70 backset 80 backset 90 1 5A504 60 0 1 5A504 70 0 1 5A504 80 0 1 5A504 90 0
 <ul style="list-style-type: none"> • Rounded faceplate in satin nickel-plated steel • 16mm deadbolt • Faceplate: 22 mm • Throws: 1) • Centre distance: 85 mm 	backset 60 backset 70 backset 80 backset 90 1 5A504 60 0 12 1 5A504 70 0 12 1 5A504 80 0 12 1 5A504 90 0 12

