


Luminaire Structure

- Stainless steel body in grade 316
- Single cable entry
- One cable gland supplied with 2 m of 2x1.0 sqmm outdoor cable
- Stainless steel fasteners in grade 316
- Durable silicone rubber gasket
- Clear toughened glass
- Remote driver (included)
- Luminaire must be submerged when operational
- Remote box IP-rated is not included
- Maximum depth 2 m
- Outdoor cable needs to be ordered with a specific length




Product description

Without remote box IP-rated - With remote driver -
Constant current (CC) 700 mA




Light symbol



W

Product colour



Technical information

Light source	9 LED
Light source type	LED
Dimming type	DALI, 1-10V, On/Off
Material	Stainless Steel
Weight	1.4 kg
Operating temperature	-20 °C to 40 °C


Luminaire	
Power	23 W
Lumen	1923 - 2437 lm
Efficacy	84 - 106 lm/W
CCT / CRI	3000K CRI80, 4000K CRI80
Drive current	700 mA

Optic	E [14°x43°], M [17°, N [11°], VW [71°], W [32°]
Bug	B2-U0-G0, B3-U0-G0
ULR	0%
ULOR	0%
CIE flux code n°3	100
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hours)	90,000
Lifetime L80B10 (hours)	100,000
Lifetime L80B50 (hours)	140,000


Accessories



Colour filter (Red)




Colour filter (Green)



Colour filter (Yellow)



Colour filter (Blue)



Honeycomb louvre



Remote box IP65
